## **EXEOR TIG MultiLock TM-Series**

## Flexible TIG welding torches





**Industry** 

- Aerospace
- Automotive
- Food and Beverage
- Light Fabrication
- Marine and Offshore
- Petrochemical
- Pipeline
- Steel Industry
- Tank and Vessel Fabrication

The innovative Exeor TIG torch range is designed to provide excellent ergonomics and outstanding performance in TIG welding applications. With the MultiLock torch heads and on-torch remote current control options, Exeor TIG torches are a versatile choice that provides convenience in all applications. The slim, compact design, ergonomic handle with its uniquely contoured ESAB pattern and soft grip zones assures a safe and relaxed grip. The long trigger is designed to ensure a natural, easy control of the torch in all hand positions.

Choose between gas-cooled or liquid-cooled and multiple TIG body options to suit your individual application.

- Ergonomically formed handle with soft grip zones
- Long trigger as standard for easy access and control
- Optional potentiometer for additional parameter control
- Easy change between the compact SR 9/20/21 torch head or the larger, more durable SR 17/18/26 torch head
- Plug & Play connection to your ESAB TIG machine without additional configuration

Visit **esab.com** for more information.



Choose between standard one-trigger version or potentiometer version for easy access to adjustment of welding parameters.

## XA00293520 GL/EN 03/2024 ESAB reserves the right to alter product images and specifications without prior notice. Product images may not be an exact representation.

## **EXEOR TIG MultiLock TM-Series**

| Specifications          |                             |                              |  |  |  |
|-------------------------|-----------------------------|------------------------------|--|--|--|
|                         | TM 125 (with SR 9/21 head)  | TM 250 (with SR 9/21 head)   |  |  |  |
| Welding Output (10 min) | 35%<br>120 A AC<br>170 A DC | 100%<br>155 A AC<br>220 A DC |  |  |  |
| Rec. Electrode Ø        | 0.5-2.4 mm                  | 0.5-3.2 mm                   |  |  |  |
| Cable Length            | 4m, 8 m                     | 4m, 8 m                      |  |  |  |
| Cooling                 | Gas                         | Liquid                       |  |  |  |
| Certification Mark      | CE                          |                              |  |  |  |

| Ordering Information   |        |           |               |         |            |            |  |
|--|--------|-----------|---------------|---------|------------|------------|--|
|  | Handle | Connector | Module        | Cooling | 4 m        | 8 m        |  |
| Exeor TIG TM 125   | Small  | 2-pin     | Trigger       | Gas     | 0700026260 | 0700026261 |  |
| Exeor TIG TM 250   | Small  | 2-pin     | Trigger       | Liquid  | 0700026320 | 0700026321 |  |
|  |        |           |               |         |            |            |  |
| Potentiometer versions for Rebel-, Rogue ET-, Renegade ET*- and Fabricator ET series |        |           |               |         |            |            |  |
| Exeor TIG TM 125-R   | Small  | 8-pin     | Potentiometer | Gas     | 0700026274 | 0700026275 |  |
| Exeor TIG TM 250-R   | Small  | 8-pin     | Potentiometer | Liquid  | 0700026324 | 0700026325 |  |

<sup>\*</sup> Not applicable for Rebel EMP 215iC and Renegade ET 300i/300iP.

R = Potentiometer for remote control

Please see separate fact sheet for wear parts.

| Accessories                       |            |  |  |
|-----------------------------------|------------|--|--|
| MultiLock Torch Head, SR 9/20/21  | 402P550002 |  |  |
| MultiLock Torch Head, SR 17/18/26 | 402P550003 |  |  |

Standard MultiLock torches comes with SR9/20/21 torch head and consumables for 2.4mm wear part kit.



ESAB / esab.com







